

HobbyCam

Lashing systems

DESCRIPTION AND FEATURES

Hobbistic high tenacity polyester lashing system with cambuckle, which is sewn to the webbing to manually adjust its tension with great simplicity, obtaining a ring closure.

This construction offers optimal load holding in every area of application and at the same time prevents damage due to overtightening, often caused by the improper use of tensioning ratchets.

The polyester fibre gives excellent resistance to breakage, mineral acids, weathering and abrasion with very low elongation.

The sewings are managed by expert craftsmen to ensure maximum safety and reliability even after continuous use.

It is certified and complies with the European standard UNI EN 12195-2.

USE

Leisure: suitable for securing packagings and light loads on cars, motorcycles and bicycles and for properly securing furnitures during transport.

NOTES

Other colours, heights and lengths available on request.



The data in the table are indicative and subject to change without notice

Code	Height mm.	Breaking load daN	Length mt.	Packaging type	Colour
622.12150	25	250	1,5	single shrink film	orange (1)
622.12250	25	250	2,5	single shrink film	orange
622.12300	25	250	3	single shrink film	orange
622.12400	25	250	4	single shrink film	orange
622.12500	25	250	5	single shrink film	orange
622.15150	25	250	1,5	single shrink film	blue (2)
622.15250	25	250	2,5	single shrink film	blue
622.15300	25	250	3	single shrink film	blue
622.15400	25	250	4	single shrink film	blue
622.15500	25	250	5	single shrink film	blue



COLOURS

1



2

