

Security 66

Twisted ropes

DESCRIPTION AND FEATURES

3 strands high tenacity nylon double twisted rope, a synthetic fibre that ensures excellent resistance to breakage and weather with low elongation. Its structure makes it easy to splice and keeps it soft and easy to handle even after use. Compared to the SeaMaster HT, this semi-sinking rope has an approx. 30% higher breaking load and a moderately lower elongation coefficient.

USE

Industry and construction: suitable for securing and lifting heavy loads and as a safety rope on construction sites.
Nautical: suitable for medium and large boats mooring and anchoring and on-board equipment.

NOTES

Other diameters and packagings available on request.

The data in the table are indicative and subject to change without notice

Code	Ø mm.	Weight gr./mt.	Breaking load kg.	Packaging type	Length mt.	Colour
133.10006	6	24	750	flang. reel	200	white/coloured stripes
133.10008	8	42	1350	flang. reel	200	white/coloured stripes
133.10010	10	65	2080	flang. reel	200	white/coloured stripes
133.10012	12	94	3000	flang. reel	200	white/coloured stripes
133.10014	14	128	4100	flang. reel	100	white/coloured stripes
133.10016	16	166	5300	flang. reel	100	white/coloured stripes
133.10018	18	210	6700	flang. reel	100	white/coloured stripes
133.10020	20	260	8400	flang. reel	100	white/coloured stripes
133.10022	22	315	10000	flang. reel	100	white/coloured stripes
133.10024	24	375	12000	flang. reel	100	white/coloured stripes
133.10026	26	440	13900	flang. reel	100	white/coloured stripes
133.10028	28	510	15800	flang. reel	100	white/coloured stripes
133.10030	30	585	17900	flang. reel	100	white/coloured stripes
133.10032	32	665	20000	flang. reel	100	white/coloured stripes
133.10034	34	750	22400	flang. reel	100	white/coloured stripes
133.10036	36	840	24800	flang. reel	100	white/coloured stripes
133.10038	38	960	27400	flang. reel	100	white/coloured stripes
133.10040	40	1070	30000	flang. reel	100	white/coloured stripes

COLOURS

