SyntHemp

Twisted ropes

DESCRIPTION AND FEATURES

3 strands high tenacity spun polypropylene twisted rope with anti-UV stabilizing treatment, a synthetic fibre that gives good resistance to breakage and weather with reduced elongation.

Extremely light, its structure makes it easy to splice and keeps it soft and easy to handle even after use. Thanks to its hemp-like Colour and woolly appearance, it is an excellent substitute for natural fibre ropes as it does not rot in the elements and does not require any maintenance, ensuring maximum grip and hold both wet and

Compared to the OldStyle, this floating rope offers better value for money by being cheaper.

USE

Decoration: suitable for creating environments, scenographies, coverings, windows dressing, handrails for stairs, setting up piers, delimitation of areas, handicrafts and decoration of vintage boats.

Nautical: suitable for on-board equipment, decking and deck fittings. Leisure: suitable for mounting hammocks and swings.

NOTES

Other diameters and packagings available on request.



The data in the table are indicative and subject to change without notice

Ø mm.	Weight gr./mt.	Breaking load kg.	Packaging type	Length mt.	Colour
4	6,2	170	roll	220	hemp
6	16	350	roll	220	hemp
8	28	600	roll	220	hemp
10	43	900	roll	220	hemp
12	63	1340	roll	220	hemp
14	81	1740	roll	220	hemp
16	104	2180	roll	220	hemp
18	130	2730	roll	220	hemp
20	160	3420	roll	220	hemp
24	230	4830	roll	220	hemp
26	270	5750	roll	220	hemp
28	310	6500	roll	220	hemp
32	400	8300	roll	220	hemp
36	510	10400	roll	220	hemp
40	630	12900	roll	220	hemp
	mm. 4 6 8 10 12 14 16 18 20 24 26 28 32 36	mm. gr./mt. 4 6,2 6 16 8 28 10 43 12 63 14 81 16 104 18 130 20 160 24 230 26 270 28 310 32 400 36 510	mm. gr./mt. load kg. 4 6,2 170 6 16 350 8 28 600 10 43 900 12 63 1340 14 81 1740 16 104 2180 18 130 2730 20 160 3420 24 230 4830 26 270 5750 28 310 6500 32 400 8300 36 510 10400	mm. gr./mt. load kg. type 4 6,2 170 roll 6 16 350 roll 8 28 600 roll 10 43 900 roll 12 63 1340 roll 14 81 1740 roll 16 104 2180 roll 18 130 2730 roll 20 160 3420 roll 24 230 4830 roll 26 270 5750 roll 28 310 6500 roll 32 400 8300 roll 36 510 10400 roll	mm. gr/mt. load kg. type mt. 4 6,2 170 roll 220 6 16 350 roll 220 8 28 600 roll 220 10 43 900 roll 220 12 63 1340 roll 220 14 81 1740 roll 220 16 104 2180 roll 220 18 130 2730 roll 220 20 160 3420 roll 220 24 230 4830 roll 220 26 270 5750 roll 220 28 310 6500 roll 220 32 400 8300 roll 220 36 510 10400 roll 220





