

SeaMaster HT

Twisted ropes

DESCRIPTION AND FEATURES

3 strands high tenacity polyester double twisted rope, a synthetic fibre that ensures excellent resistance to breakage, abrasion and weather with reduced elongation.

Its structure makes it easy to splice and keeps it soft and easy to handle even after use.

This sinking rope outperforms the cheapest version (SeaMaster MT) in performance, ensuring maximum reliability in all conditions of use.

It is also available in practical cut to size skeins spliced with stainless steel thimble on one side or with one loop (SeaMaster HT Spliced).

USE

Nautical: suitable for small, medium and large boats mooring and anchoring, on-board equipment and setting up piers. Decoration: suitable for creating environments, coverings, windows dressing, delimitation of areas.

In thinner diameters it is also used as a fender rope.

Industry and construction: suitable for securing and lifting heavy loads.

NOTES

Other colours, diameters and packagings available on request.

The data in the table are indicative and subject to change without notice

Code 1 white	Code 2 black	Code 3 navy blue	Code 4 hemp	Ø mm.	Weight gr./mt.	Br. load kg.	Packaging type	Length mt.
132.10006	132.20006	132.30006	132.40006	6	26	700	flang. reel	300
132.10008	132.20008	132.30008	132.40008	8	45	1270	flang. reel	200
132.10010	132.20010	132.30010	132.40010	10	75	1680	flang. reel	200
132.10012	132.20012	132.30012	132.40012	12	110	2800	flang. reel	200
132.10014	132.20014	132.30014	132.40014	14	140	3600	flang. reel	100
132.10016	132.20016	132.30016	132.40016	16	170	4300	flang. reel	100
132.10018	132.20018	132.30018	132.40018	18	200	5400	flang. reel	100
132.10020	132.20020	132.30020	132.40020	20	280	6700	flang. reel	100
132.10022	132.20022	132.30022	132.40022	22	330	8300	flang. reel	100
132.10024	132.20024	132.30024	132.40024	24	390	9700	flang. reel	100
132.10026	132.20026	132.30026	132.40026	26	500	11100	flang. reel	100
132.10028	132.20028	132.30028	132.40028	28	600	12100	flang. reel	100
132.10030	132.20030	132.30030	132.40030	30	680	13400	flang. reel	100
132.10032	132.20032	132.30032	132.40032	32	780	15400	flang. reel	100
132.10034	132.20034	132.30034	132.40034	34	840	17100	flang. reel	100
132.10036	132.20036	132.30036	132.40036	36	930	19000	flang. reel	100
132.10038	132.20038	132.30038	132.40038	38	1050	21900	flang. reel	100
132.10040	132.20040	132.30040	132.40040	40	1300	23500	flang. reel	100

COLOURS

