

Atlantic

Braided and double braided ropes

DESCRIPTION AND FEATURES

High tenacity double braided rope, a synthetic fibre that gives excellent resistance to breakage and weather with low elongation. The pre-stretched 16/24 spindle diamond construction process with opposing and balanced anti-turn twists of both the outer cover and the internal braided core makes it flexible and compact, guarantees high abrasion resistance and keeps it soft and easy to handle even after intense and prolonged use. This sinking double braided rope is spliceable with medium difficulty and is suitable for all those technical uses where maximum reliability, a great tear absorption capacity and high wear resistance are essential requirements.

USE

Nautical: suitable as a sheet and halyard for cruising boats.
Industry and construction: suitable for securing and lifting heavy loads, for tensile structures and use with pulleys and hoists.
Theatrical uses: suitable for the creation of sets and lifting of wings, skies and backdrops thanks to its adherence and silence in the sliding phase on pulleys.

NOTES

Other colours, diameters and packagings available on request.

The data in the table are indicative and subject to change without notice

Code 1 white yellow/blk	Code 2 white red/black	Code 3 white green/black	Code 4 white l. blue/blk	Ø mm.	Weight gr./mt.	Break. load kg.	Packaging type	Length mt.
222.10003	222.20003	222.30003	222.40003	3	9	250	flanged reel	200
222.10004	222.20004	222.30004	222.40004	4	13	390	flanged reel	200
222.10005	222.20005	222.30005	222.40005	5	23	590	flanged reel	200
222.10006	222.20006	222.30006	222.40006	6	29	980	flanged reel	200
222.10008	222.20008	222.30008	222.40008	8	50	1550	flanged reel	200
222.10010	222.20010	222.30010	222.40010	10	80	2400	flanged reel	200
222.10012	222.20012	222.30012	222.40012	12	115	3200	flanged reel	200

Code 5 hemp	Code 6 grey	Code 7 navy blue	Code 8 black	Ø mm.	Weight gr./mt.	Break. load kg.	Packaging type	Length mt.
222.50003	222.60003	222.70003	222.80003	3	9	250	flanged reel	200
222.50004	222.60004	222.70004	222.80004	4	13	390	flanged reel	200
222.50005	222.60005	222.70005	222.80005	5	23	590	flanged reel	200
222.50006	222.60006	222.70006	222.80006	6	29	980	flanged reel	200
222.50008	222.60008	222.70008	222.80008	8	50	1550	flanged reel	200
222.50010	222.60010	222.70010	222.80010	10	80	2400	flanged reel	200
222.50012	222.60012	222.70012	222.80012	12	115	3200	flanged reel	200

COLOURS

