

PolyRope

Twisted ropes

DESCRIPTION AND FEATURES

3 strands polypropylene twisted rope with anti-UV stabilizing treatment, a synthetic fibre that offers lightness, good resistance to breakage and weather with moderate elongation.

Its structure makes it easy to splice and offers a good balance between strength and flexibility, keeping it easy to handle even after use.

It is floating and among the twisted ropes it is the one that offers the best value for money based on the metric weight.

USE

Agriculture: suitable for securing tarpaulins in greenhouses and tying plants.

Food uses: suitable and certified for direct contact with food (white colour).

Nautical: suitable for long moorings and boat towing (orange colour).

Industry: suitable for packagings.

NOTES

Other diameters and packagings available on request.

The data in the table are indicative and subject to change without notice

Code 1 white	Code 2 orange	Ø mm.	Weight gr./mt.	Breaking load kg.	Packaging type	Length mt.
124.00004	124.10004	4	8	320	roll	500
124.00005	124.10005	5	12	470	roll	400
124.00006	124.10006	6	18	600	roll	300
124.00008	124.10008	8	30	1080	flanged reel	200
124.00010	124.10010	10	45	1580	flanged reel	200
124.00012	124.10012	12	65	2210	flanged reel	200
124.00014	124.10014	14	90	3050	flanged reel	200
124.00016	124.10016	16	115	3770	flanged reel	200
124.00018	124.10018	18	148	4810	flanged reel	200
124.00020	124.10020	20	180	5800	flanged reel	200
124.00022	124.10022	22	220	6950	flanged reel	200
124.00024	124.10024	24	260	8125	flanged reel	200
124.00026	124.10026	26	305	9400	roll	200
124.00028	124.10028	28	355	10705	roll	200
124.00030	124.10030	30	405	12230	roll	200
124.00032	124.10032	32	460	13455	roll	200
124.00034	124.10034	34	523	15188	roll	200
124.00036	124.10036	36	585	16920	roll	200
124.00038	124.10038	38	653	17805	roll	200
124.00040	124.10040	40	720	20490	roll	200

COLOURS

1



2

