

Scirocco

Braided and double braided ropes

DESCRIPTION AND FEATURES

High tenacity double braided rope, a synthetic fibre that gives excellent resistance to breakage and weather with low elongation.

The pre-stretched 16/24 spindle construction process with opposing and balanced anti-turn twists of both the outer cover and the internal braided core makes it flexible and compact, guarantees high abrasion resistance and keeps it soft and easy to handle even after intense and prolonged use.

This sinking double braided rope is spliceable with medium difficulty and is suitable for all those technical uses where maximum reliability, a great tear absorption capacity and high wear resistance are essential requirements.

USE

Nautical: suitable as a sheet and halyard for cruising boats.

Theatrical uses: suitable for the creation of sets and lifting of wings, skies and backdrops thanks to its adherence and silence in the sliding phase on pulleys.

Industry and construction: suitable for securing and lifting heavy loads, for tensile structures and use with pulleys and hoists.

NOTES

Other colours, diameters and packagings available on request.

The data in the table are indicative and subject to change without notice

Code 1 yellow black strip.	Code 2 red black strip.	Code 3 green black strip.	Code 4 light blue black strip.	Ø mm.	Weight gr./mt.	Break. load kg.	Packaging type	Length mt.
224.10003	224.20003	224.30003	224.40003	3	10	270	flanged reel	200
224.10004	224.20004	224.30004	224.40004	4	13	390	flanged reel	200
224.10005	224.20005	224.30005	224.40005	5	23	590	flanged reel	200
224.10006	224.20006	224.30006	224.40006	6	29	980	flanged reel	200
224.10008	224.20008	224.30008	224.40008	8	50	1550	flanged reel	200
224.10010	224.20010	224.30010	224.40010	10	80	2400	flanged reel	200
224.10012	224.20012	224.30012	224.40012	12	115	3200	flanged reel	200
224.10014	224.20014	224.30014	224.40014	14	145	4400	flanged reel	200
224.10016	224.20016	224.30016	224.40016	16	170	5600	flanged reel	200

Code 5 navy blue	Code 6 hemp	Code 7 black	Code 8 grey	Ø mm.	Weight gr./mt.	Break. load kg.	Packaging type	Length mt.
224.50003	224.60003	224.70003	224.80003	3	10	270	flanged reel	200
224.50004	224.60004	224.70004	224.80004	4	13	390	flanged reel	200
224.50005	224.60005	224.70005	224.80005	5	23	590	flanged reel	200
224.50006	224.60006	224.70006	224.80006	6	29	980	flanged reel	200
224.50008	224.60008	224.70008	224.80008	8	50	1550	flanged reel	200
224.50010	224.60010	224.70010	224.80010	10	80	2400	flanged reel	200
224.50012	224.60012	224.70012	224.80012	12	115	3200	flanged reel	200
224.50014	224.60014	224.70014	224.80014	14	145	4400	flanged reel	200
224.50016	224.60016	224.70016	224.80016	16	170	5600	flanged reel	200

COLOURS

