

# LightBraid

## Braided and double braided ropes

### DESCRIPTION AND FEATURES

High tenacity polypropylene braided rope with anti-UV stabilizing treatment, a synthetic fibre that gives good resistance to breakage and weather with moderate elongation. The 16 spindle construction process allows an excellent knot hold and keeps it soft and easy to handle even after use.

For common uses where aesthetic impact is prioritized over performance, the LightBraid represents the best value for money.

### USE

Leisure: suitable for making skippers, for tying and non-heavy general uses.  
 Decoration: suitable for coverings, windows dressing, creating environments and making handicrafts.

### NOTES

Other colours, diameters and packagings available on request.



The data in the table are indicative and subject to change without notice

| Code 1<br>white | Code 2<br>yellow | Code 3<br>red | Ø<br>mm. | Weight<br>gr./mt. | Breaking<br>load kg. | Packaging<br>type | Length<br>mt. |
|-----------------|------------------|---------------|----------|-------------------|----------------------|-------------------|---------------|
| 244.10004       | 244.20004        | 244.30004     | 4        | 10                | 240                  | flanged reel      | 200           |
| 244.10005       | 244.20005        | 244.30005     | 5        | 14                | 360                  | flanged reel      | 200           |
| 244.10006       | 244.20006        | 244.30006     | 6        | 21                | 500                  | flanged reel      | 200           |
| 244.10008       | 244.20008        | 244.30008     | 8        | 38                | 700                  | flanged reel      | 200           |
| 244.10010       | 244.20010        | 244.30010     | 10       | 63                | 1000                 | flanged reel      | 200           |
| 244.10012       | 244.20012        | 244.30012     | 12       | 85                | 1300                 | flanged reel      | 200           |

| Code 4<br>green | Code 5<br>light blue | Code 6<br>black | Ø<br>mm. | Weight<br>gr./mt. | Breaking<br>load kg. | Packaging<br>type | Length<br>mt. |
|-----------------|----------------------|-----------------|----------|-------------------|----------------------|-------------------|---------------|
| 244.40004       | 244.50004            | 244.60004       | 4        | 10                | 240                  | flanged reel      | 200           |
| 244.40005       | 244.50005            | 244.60005       | 5        | 14                | 360                  | flanged reel      | 200           |
| 244.40006       | 244.50006            | 244.60006       | 6        | 21                | 500                  | flanged reel      | 200           |
| 244.40008       | 244.50008            | 244.60008       | 8        | 38                | 700                  | flanged reel      | 200           |
| 244.40010       | 244.50010            | 244.60010       | 10       | 63                | 1000                 | flanged reel      | 200           |
| 244.40012       | 244.50012            | 244.60012       | 12       | 85                | 1300                 | flanged reel      | 200           |

### COLOURS

