

DockLine

Braided and double braided ropes

DESCRIPTION AND FEATURES

Double braided rope with high tenacity polyester external cover and high tenacity nylon braided inner core, a construction that gives excellent tensile strength and weather resistance with low elongation. The 16/24 spindle pre-stretched construction process with opposing and balanced anti-turn twists makes it spliceable with medium difficulty, guarantees high abrasion resistance and keeps it very soft and easy to handle even after intense and prolonged use. This sinking double braided rope guarantees excellent performance for any technical application.

USE

Nautical: suitable for medium and large boats mooring and anchoring, it guarantees high absorption of wave motion stresses and reduces those transmitted to the boat.

In thinner diameters it is used as a fender rope.

Industry: suitable for fastening and lifting heavy loads, use with pulleys and hoists and for tensile structures.

Decoration: suitable for windows dressing, coverings and creating environments.

NOTES

Other colours, diameters and packagings available on request.

The data in the table are indicative and subject to change without notice

Code 1 black	Code 2 navy blue	Ø mm.	Weight gr./mt.	Breaking load kg.	Packaging type	Length mt.
212.20008	212.30008	8	48	1600	flanged reel	200
212.20010	212.30010	10	78	2400	flanged reel	200
212.20012	212.30012	12	115	3500	flanged reel	200
212.20014	212.30014	14	140	4200	flanged reel	200
212.20016	212.30016	16	180	5000	flanged reel	100
212.20018	212.30018	18	220	5500	flanged reel	100
212.20020	212.30020	20	250	8600	flanged reel	100
212.20022	212.30022	22	310	11700	flanged reel	100
212.20024	212.30024	24	380	13700	flanged reel	100
212.20026	212.30026	26	490	14900	flanged reel	100

COLOURS

1



2

