

DynExtreme SK75

Braided and double braided ropes

DESCRIPTION AND FEATURES

Dyneema® SK75 (HMPE) braided rope, a synthetic fibre that guarantees extreme lightness and tensile strength with almost non-existent elongation.

The 12 spindle construction process makes it extremely compact and keeps it easy to handle even after intense and prolonged use.

The urethane protective treatment allows a long life and excellent resistance to weather, drastically reducing water absorption.

This special braided rope is very light, easy to splice and is suitable to meet the most extreme needs, being more resistant than steel and weighing much less for the same diameter.

USE

Nautical: suitable as a sheet and halyard for cruising and racing boats, for use in chokes and pulleys.

In smaller diameters it is used as a line for spearguns, windsurfing and kitesurfing.

Industry and construction: suitable for use with pulleys and hoists, fastening and lifting extremely heavy loads and for tensile structures.

Leisure: suitable as a tow line for winches in quads, jeeps and off-road vehicles as a replacement for the classic steel cable.

NOTES

Other colours, diameters and packagings available on request.



COLOURS



The data in the table are indicative and subject to change without notice

Code 1 white	Code 2 yellow	Code 3 red	Ø mm.	Weight gr./mt.	Breaking load kg.	Packaging type	Length mt.
229.10001	229.20001	229.30001	1	1,2	190	flanged reel	100
229.10013	229.20013	229.30013	1,3	1,5	350	flanged reel	100
229.10015	229.20015	229.30015	1,5	2	480	flanged reel	100
229.10002	229.20002	229.30002	2	3,5	900	flanged reel	100
229.10003	229.20003	229.30003	3	5	1200	flanged reel	100
229.10004	229.20004	229.30004	4	14	1900	flanged reel	100
229.10005	229.20005	229.30005	5	20	2900	flanged reel	100
229.10006	229.20006	229.30006	6	28	4400	flanged reel	100
229.10007	229.20007	229.30007	7	38	6500	flanged reel	100
229.10008	229.20008	229.30008	8	42	7600	flanged reel	100
229.10009	229.20009	229.30009	9	46	9700	flanged reel	100
229.10010	229.20010	229.30010	10	61	12300	flanged reel	100
229.10012	229.20012	229.30012	12	93	14700	flanged reel	100
229.10014	229.20014	229.30014	14	120	18200	flanged reel	100

Code 4 light blue	Code 5 grey	Code 6 black	Ø mm.	Weight gr./mt.	Breaking load kg.	Packaging type	Length mt.
229.40001	229.50001	229.60001	1	1,2	190	flanged reel	100
229.40013	229.50013	229.60013	1,3	1,5	350	flanged reel	100
229.40015	229.50015	229.60015	1,5	2	480	flanged reel	100
229.40002	229.50002	229.60002	2	3,5	900	flanged reel	100
229.40003	229.50003	229.60003	3	5	1200	flanged reel	100
229.40004	229.50004	229.60004	4	14	1900	flanged reel	100
229.40005	229.50005	229.60005	5	20	2900	flanged reel	100
229.40006	229.50006	229.60006	6	28	4400	flanged reel	100
229.40007	229.50007	229.60007	7	38	6500	flanged reel	100
229.40008	229.50008	229.60008	8	42	7600	flanged reel	100
229.40009	229.50009	229.60009	9	46	9700	flanged reel	100
229.40010	229.50010	229.60010	10	61	12300	flanged reel	100
229.40012	229.50012	229.60012	12	93	14700	flanged reel	100
229.40014	229.50014	229.60014	14	120	18200	flanged reel	100