

TruckFix PRO

Lashing systems

DESCRIPTION AND FEATURES

Professional high tenacity polyester lashing system, available in the ring version (without hooks) or with two hooks sewn at the end of the webbing ("J" shaped, chassis, triangle and tendex) and equipped with a hardened steel ratchet to manually adjust its tension in a incremental and safe way.

The polyester fibre gives excellent resistance to breakage, mineral acids, weathering and abrasion with very low elongation.

The sewings are managed by expert craftsmen to ensure maximum safety and reliability even after continuous and heavy use.

It is certified and complies with the European standard UNI EN 12195-2.

USE

Industry and construction: suitable for securing demanding, bulky and heavy loads, securing all types of materials on vans, trucks, aircrafts, containers, trolleys and platforms and for anchoring and securing tensile structures.

NOTES

Other colours, lengths and capacities available on request.



The data in the table are indicative and subject to change without notice

Code	Height mm.	Breaking load daN	Length mt.	Hook type	Packaging type	Colour
605.4362060	35	1000/2000	5,5 + 0,5	claw (1)	single shrink film	orange
605.4363060	35	1000/2000	5,5 + 0,5	chassis (2)	single shrink film	orange
605.4361060	35	1000/2000	6	none (ring)	single shrink film	orange
608.4966090	50	2000/4000	8,5 + 0,5	claw	single shrink film	orange
608.4967090	50	2000/4000	8,5 + 0,5	chassis	single shrink film	orange
608.4968090	50	2000/4000	8,5 + 0,5	triangle (3)	single shrink film	orange
608.4972050	50	2000/4000	3 + 2	tendex (4)	single shrink film	orange
608.4964090	50	2000/4000	9	none (ring)	single shrink film	orange

COLOURS

