

RoundLine HT

Braided and double braided ropes

DESCRIPTION AND FEATURES

12 strands high tenacity polyester braided rope, a synthetic fibre that gives excellent resistance to breakage and weather with low elongation.

The double twisted construction process with opposing and balanced anti-turn twists makes it easy to splice and guarantees high wear resistance.

Compared to the 3 strands twisted ropes (SeaMaster MT and HT), this sinking braided rope remains very soft and flexible even after intense and prolonged use over time. It is also available in practical cut to size skeins spliced with stainless steel thimble on one side or with one loop (RoundLine HT Spliced).

USE

Nautical: suitable for setting up piers, any size boats mooring and anchoring (also large yachts), it guarantees high absorption of wave motion stresses and reduces those transmitted to the boat. In thinner diameters it is used as a fender rope.

Decoration: suitable for windows dressing, coverings, handrails and creating environments.

Industry: suitable for securing and lifting heavy loads and use with pulleys and hoists.

NOTES

Other colours, diameters and packagings available on request.

The data in the table are indicative and subject to change without notice

Code 1 white	Code 2 black	Code 3 navy blue	Ø mm.	Weight gr./mt.	Breaking load kg.	Packaging type	Length mt.
205.10008	205.20008	205.30008	8	43	1700	flanged reel	200
205.10010	205.20010	205.30010	10	70	2300	flanged reel	200
205.10012	205.20012	205.30012	12	100	2800	flanged reel	200
205.10014	205.20014	205.30014	14	135	3600	flanged reel	200
205.10016	205.20016	205.30016	16	165	4200	flanged reel	150
205.10018	205.20018	205.30018	18	205	5100	flanged reel	150
205.10020	205.20020	205.30020	20	250	6000	flanged reel	100
205.10022	205.20022	205.30022	22	290	7200	flanged reel	100
205.10024	205.20024	205.30024	24	330	8400	flanged reel	100
205.10026	205.20026	205.30026	26	360	9400	flanged reel	100
205.10028	205.20028	205.30028	28	460	11000	flanged reel	100
205.10030	205.20030	205.30030	30	520	12400	flanged reel	100
205.10032	205.20032	205.30032	32	590	13700	flanged reel	100

COLOURS

1



2



3

