

RoundLine HT Spliced Ropes with accessories

DESCRIPTION AND FEATURES

12 strands high tenacity polyester braided rope, a synthetic fibre that gives excellent resistance to traction and weather with low elongation.

The double twisted construction process with opposing and balanced anti-turn twists makes it easy to splice and guarantees high wear resistance.

Each skein is heat cutted to measure by expert craftsmen on both sides and spliced on one side with a stainless steel thimble or buttonhole.

USE

Nautical: suitable for small, medium and large boats mooring and anchoring and on-board equipment.

NOTES

Other colours and diameters available on request.



The data in the table are indicative and subject to change without notice

Code 1 white	Code 2 black	Code 3 navy blue	Ø mm.	Weight gr./mt.	Br. load kg.	Packaging type	Final type
726.108**	726.208**	726.308**	8	43	1700	skein	1 loop
726.110**	726.210**	726.310**	10	70	2300	skein	1 loop
726.112**	726.212**	726.312**	12	100	2800	skein	1 loop
726.114**	726.214**	726.314**	14	135	3600	skein	1 loop
726.116**	726.216**	726.316**	16	165	4200	skein	1 loop
726.118**	726.218**	726.318**	18	205	5100	skein	1 loop
726.120**	726.220**	726.320**	20	250	6000	skein	1 loop
727.108**	727.208**	727.308**	8	43	1700	skein	1 inox thimble
727.110**	727.210**	727.310**	10	70	2300	skein	1 inox thimble
727.112**	727.212**	727.312**	12	100	2800	skein	1 inox thimble
727.114**	727.214**	727.314**	14	135	3600	skein	1 inox thimble
727.116**	727.216**	727.316**	16	165	4200	skein	1 inox thimble
727.118**	727.218**	727.318**	18	205	5100	skein	1 inox thimble
727.120**	727.220**	727.320**	20	250	6000	skein	1 inox thimble

** Length mt. on request.

COLOURS

