

# DynePower SK75

## Braided and double braided ropes

### DESCRIPTION AND FEATURES

Braided rope with a mix of high tenacity spun polyester and Dyneema® SK75 (HMPE) impregnated with protective polyurethane resin, a construction that guarantees maximum lightness and tensile strength with very low elongation. The 12 spindle construction process makes it flexible, compact and keeps it soft and easy to handle even after intense and prolonged use.

The spun polyester guarantees excellent grip and the protective urethane treatment allows a long life and excellent resistance to weather, drastically reducing water absorption.

This braided rope is spliceable with medium difficulty and is suitable for all those specific technical uses where maximum level performance, stability and reliability are required.

### USE

Nautical: suitable as a sheet and halyard for cruising and racing boats, as a spi and mainsail sheet.

### NOTES

Other colours, diameters and packagings available on request.

The data in the table are indicative and subject to change without notice

Code 1 white yellow	Code 2 white red	Code 3 white blue	Ø mm.	Weight gr./mt.	Breaking load kg.	Packaging type	Length mt.
228.10045	228.20045	228.30045	4/5	10	600	flanged reel	100
228.10067	228.20067	228.30067	6/7	25	2200	flanged reel	100
228.10089	228.20089	228.30089	8/9	35	3400	flanged reel	100
228.11011	228.21011	228.31011	10/11	55	4700	flanged reel	100

### COLOURS

1



2



3

