

ErgoFix PRO

Lashing systems

DESCRIPTION AND FEATURES

Professional high tenacity polyester lashing system, available in the ring version (without hooks) or with two hooks sewn at the end of the webbing ("J" shaped, chassis and triangle) and equipped with a hardened steel ratchet to manually adjust its tension in a incremental and safe way.

Acting on the handle from top to bottom it is possible to aspsindle great force in an easy way, securing loads perfectly.

The polyester fibre gives excellent resistance to breakage, mineral acids, weathering and abrasion with very low elongation.

The sewings are managed by expert craftsmen to ensure maximum safety and reliability even after continuous and heavy use.

It is certified and complies with the European standard UNI EN 12195-2.

USE

Industry and construction: suitable for securing demanding, bulky and heavy loads, securing all types of material on vans, trucks, aircraft, containers, trolleys and platforms and for anchoring and securing tensile structures.

NOTES

Other colours, lengths and capacities available on request.

The data in the table are indicative and subject to change without notice

Code	Height mm.	Breaking load daN	Length mt.	Type di hook	Packaging type	Colour
612.5466090	50	2000/4000	8,5 + 0,5	claw (1)	single shrink film	orange
612.5467090	50	2000/4000	8,5 + 0,5	chassis (2)	single shrink film	orange
612.5468090	50	2000/4000	8,5 + 0,5	triangle (3)	single shrink film	orange
612.5464090	50	2000/4000	9	none (ring)	single shrink film	orange



COLOURS

