

Plissé

Braided and double braided ropes

DESCRIPTION AND FEATURES

High tenacity nylon braided rope, a synthetic fibre that offers excellent resistance to breakage and abrasion with low elongation. The 16/24 spindle construction process allows a high knot strength and the presence of the inner parallel core reduces the risk of crushing the braided rope. The nylon fibre guarantees high resistance to weather.

USE

Curtains: suitable for making small blinds, panel blinds and pleated blinds.

Decoration: suitable for the production of jewelry, necklaces and bracelets.

It is also used for upholstery work, for industrial sewings and technical uses.

NOTES

Other diameters and packagings available on request.

The data in the table are indicative and subject to change without notice

Code	Type	Ø mm.	Weight gr./mt.	Breaking load kg.	Packaging type	Length mt.	Colour
286.10007	Z 12	0,7	0,5	35	flanged reel	200	white
286.10011	Z 24	1,1	0,9	50	flanged reel	200	white
286.10013	Z 32	1,3	1,2	62	flanged reel	200	white
286.10016	Z 48	1,6	1,6	75	flanged reel	200	white
286.10018	Z 64	1,8	2,2	88	flanged reel	200	white
286.10021	Z 80	2,1	2,7	105	flanged reel	200	white

COLOURS

