

CamFix

Lashing systems

DESCRIPTION AND FEATURES

Hobbistic high tenacity polyester lashing system with cambuckle, which is sewn to the webbing to manually adjust its tension with great simplicity, obtaining a ring closure.

This construction offers optimal load holding in every area of application and at the same time prevents damage due to overtightening, often caused by the improper use of tensioning ratchets.

The polyester fibre gives excellent resistance to breakage, mineral acids, weathering and abrasion with very low elongation.

The sewings are managed by expert craftsmen to ensure maximum safety and reliability even after continuous use.

It is certified and complies with the European standard UNI EN 12195-2.

USE

Leisure: suitable for securing packagings and light loads on cars, motorcycles and bicycles and for properly securing furnitures during transport.

NOTES

Other colours, heights and lengths available on request.



The data in the table are indicative and subject to change without notice

Code	Height mm.	Breaking load daN	Length mt.	Packaging type	Colour
632.22250	25	250	2,5	double blister	orange (1)
632.22300	25	250	3	double blister	orange
632.22400	25	250	4	double blister	orange
632.22500	25	250	5	double blister	orange
632.25250	25	250	2,5	double blister	blue (2)
632.25300	25	250	3	double blister	blue
632.25400	25	250	4	double blister	blue
632.25500	25	250	5	double blister	blue
632.12500	25	250	5	single blister	orange
632.15500	25	250	5	single blister	blue



COLOURS

1



2

