

Scirocco Mélange

Braided and double braided ropes

DESCRIPTION AND FEATURES

High tenacity double braided rope, a synthetic fibre that gives excellent resistance to breakage and weather with low elongation. The pre-stretched 16/24 spindle construction process with opposing and balanced anti-turn twists of both the outer cover and the internal braided core makes it flexible and compact, guarantees high abrasion resistance and keeps it soft and easy to handle even after intense and prolonged use.

This sinking double braided rope is spliceable with medium difficulty and is suitable for all those technical uses where maximum reliability, a great tear absorption capacity and high wear resistance are essential requirements.

USE

Nautical: suitable as a sheet and halyard for cruising boats.
Industry and construction: suitable for securing and lifting heavy loads, for tensile structures and use with pulleys and hoists.

NOTES

Other colours, diameters and packagings available on request.



The data in the table are indicative and subject to change without notice

Code 1 yellow black	Code 2 red black	Code 3 light blue black	Code 4 grey black	Ø mm.	Weight gr./mt.	Break. load kg.	Packaging type	Length mt.
224.11003	224.12003	224.13003	224.14003	3	10	270	flanged reel	200
224.11004	224.12004	224.13004	224.14004	4	13	390	flanged reel	200
224.11005	224.12005	224.13005	224.14005	5	23	590	flanged reel	200
224.11006	224.12006	224.13006	224.14006	6	29	980	flanged reel	200
224.11008	224.12008	224.13008	224.14008	8	50	1550	flanged reel	200
224.11010	224.12010	224.13010	224.14010	10	80	2400	flanged reel	200
224.11012	224.12012	224.13012	224.14012	12	115	3200	flanged reel	200
224.11014	224.12014	224.13014	224.14014	14	145	4400	flanged reel	200
224.11016	224.12016	224.13016	224.14016	16	170	5600	flanged reel	200

Code 5 grey fluo yellow	Code 6 grey fluo orange	Code 7 grey red	Code 8 grey light blue	Ø mm.	Weight gr./mt.	Break. load kg.	Packaging type	Length mt.
224.15103	224.16103	224.12103	224.13103	3	10	270	flanged reel	200
224.15104	224.16104	224.12104	224.13104	4	13	390	flanged reel	200
224.15105	224.16105	224.12105	224.13105	5	23	590	flanged reel	200
224.15106	224.16106	224.12106	224.13106	6	29	980	flanged reel	200
224.15108	224.16108	224.12108	224.13108	8	50	1550	flanged reel	200
224.15110	224.16110	224.12110	224.13110	10	80	2400	flanged reel	200
224.15112	224.16112	224.12112	224.13112	12	115	3200	flanged reel	200
224.15114	224.16114	224.12114	224.13114	14	145	4400	flanged reel	200
224.15116	224.16116	224.12116	224.13116	16	170	5600	flanged reel	200

COLOURS

